


## Quick-Shot™ Instructions




1. Unsnap rear flaps




2. Insert belt in front of rear section




3. Close flaps and secure snaps



4. Belt should be visible from front




5. Put on belt keeping buckle to one side. (Optional: If using a standard size belt, the belt can be threaded through belt loops skipping both the first and last loops.)



6. Tighten belt as much as possible for maximum support. Re-tighten belt as necessary to maintain support.



**WARNING:** Butt of firearm must be <u>FULLY</u> inserted into the *Quick-Shot*™ to ensure proper firearm support. Always keep one or more hands on the firearm for stabilization. Do not use the *Quick-Shot™* with a loose belt, because the firearm may point in an unsafe direction.



## Care and Conditioning of your leather *Quick-Shot*™

The leather *Quick-Shot*<sup>™</sup> is not intended to be used in heavy rain or conditions where the leather may become saturated with water. Under these circumstances, the leather may become soft and lose its form. Should your leather *Quick-Shot*<sup>™</sup> become wet and soft, STOP using it immediately. Re-form the leather by hand and allow it to dry thoroughly. Then apply leather conditioner (neatsfoot oil, Lexol, etc). Periodically applying a light coat of conditioner to both sides of the leather, especially along folds/creases, will extend the life of your leather *Quick-Shot*<sup>™</sup> and improve its water resistance. The leather can also be sprayed with waterproofing agents approved for leather products.

Note: Applying oils and conditioners to your leather **Quick-Shot**<sup>™</sup> may darken its overall color. This is normal. The color will probably lighten again over time as the oil disperses throughout the leather.

